

CS-107

“Green” Closed Recirculating System Treatment

- Contains all non-hazardous components
- Prevents oxygen pitting and corrosion in systems containing iron, steel, copper and their alloys.
- Convenient, easy-to-use liquid.
- Does not contain heavy metals or nitrites.
- Compatible with glycol based antifreeze products.

General Description

CS-107 is a liquid chemical treatment formulated to prevent pitting and corrosion in closed recirculating water systems. CS-107 is recommended for hot water boilers and most closed systems. When used as recommended, CS-107 does not harm packing, valves, pumps, or mechanical seals.

Specifications

Wt/gallon:	8.5
pH (conc):	6.5-7.5
Specific gravity:	1.00
Appearance:	Clear Liquid

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Application

Initial Dosage

Add 1 gallon of CS-107 for every 100 gallons of water in the system.

Maintenance

After the initial dosage, occasional additions of **CS-107** may be required to maintain proper treatment levels. The additions will be determined by Sodium Erythorbate on-site testing and the amount of leakage from the system. Maintain Sodium Erythorbate between 2.5 - 7.5ppm. **CS-107** may be added to the closed system through a bypass feeder on the recirculating line.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.
GERMANTOWN, WI 53022

**S
P
E
C
T
R
U
M[®]**