

CS-167

Closed Recirculating System Treatment

- Molybdate based corrosion inhibitor formulated for closed systems containing Iron, Steel, and Copper.
- Synergistic inhibitor mechanism enhances protection capabilities of molybdates and copper corrosion inhibitors
- Compatible with glycol type antifreeze products.

General Description

Commonly sodium nitrite based treatments are used as closed system corrosion inhibitors. However, nitrite reducing bacteria can thrive in a nitrite treated system when the temperature provides the perfect environment. The bacteria destroys the corrosion inhibition mechanism. This will not occur with **CS-167**.

Spectrum® treatment products and programs are the key to long term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

Specifications

Wt/gallon:	9.09
pH:	9.5 - 10
Specific gravity:	1.09
Appearance	Clear, Light Amber Liquid

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Application

Initial Dosage

Add 1 gallon of **CS-167** to every 100 gallons of water in the system.

Maintenance

After the initial dosage, occasional additions of **CS-167** may be required to maintain proper treatment levels. The additions will be determined by periodic water analysis and the amount of leakage from the system. **CS-167** may be added to the closed system through a bypass feeder on the recirculating line.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.
GERMANTOWN, WI 53022

**S
P
E
C
T
R
U
M**®