

CST-20

Closed Recirculating System Treatment

- Prevents oxygen pitting and corrosion in systems containing iron, steel, copper and their alloys
- Convenient, easy-to-use liquid
- Does not contain chromates
- Compatible with glycol based antifreeze products

General Description

CST-20 is a liquid chemical treatment formulated to prevent pitting and corrosion in closed recirculating water systems. **CST-20** is recommended for hot water boilers and most closed systems. When used as recommended, **CST-20** does not harm packing, valves, pumps, or mechanical seals.

Spectrum[®] treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum**[®] a part of your preventive maintenance program today.

Specifications

Wt/gallon:	10.3 lbs.
pH:	9.6 – 10.5
Specific Gravity:	1.235
Appearance:	Light Amber, Clear Liquid

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Application

Initial Dosage:
Add 1 gallon of **CST-20** to every 200 gallons of water in the system.

Maintenance:
After the initial dosage, occasional additions of **CST-20** may be required to maintain proper treatment levels. The additions will be determined by periodic water analysis and the amount of leakage from the system. **CST-20** may be added to the closed system through a bypass feeder on the recirculating line.