

CWT-ETP

Recirculating Cooling Water Startup Treatment

- Specially formulated for Enhanced Tube Protection.
- Excellent corrosion inhibitor for copper and copper containing alloys.
- Designed for startup application, but can be used on a regular basis where additional copper corrosion inhibition is required.
- Do not mix with other water treatment chemicals.

General Description

CWT-ETP is a superior formulation designed to control corrosion in systems containing enhanced tubes or super enhanced tubes in the chiller.

CWT-ETP contains the premier corrosion inhibitor for copper and copper alloys in a single ready to use container. This product is free of chromates and heavy metals.

Spectrum® treatment products and programs are the key to long term preventative maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

Specifications

Wt/gallon:	9.92
pH:	11.5 – 12.0
Specific gravity:	1.19
Appearance:	Clear, Yellow Liquid

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Application

CWT-ETP should be used at the rate of 1 quart per 1000 gallons of make up water for the first 3-4 days of operation for protecting enhanced or super enhanced tubes. Do not mix with other water treatment compounds.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.
GERMANTOWN, WI 53022

**S
P
E
C
T
R
U
M[®]**