

OXYTROL™ LD

Feedwater Oxygen Scavenger

- Removes dissolved oxygen to inhibit oxygen pitting
- Decharacterized for USDA inspected meat and poultry plants
- Convenient, ready-to-use catalyzed liquid

General Description

Oxytrol LD is a catalyzed oxygen scavenger formulated to remove oxygen from steam boiler systems with operating pressure up to 600 psi. **Oxytrol LD** is decharacterized to meet USDA regulations for meat and poultry plants.

Spectrum® treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

Specifications

Wt/Gallon:	9.5 lbs.
pH:	4.3 – 4.7
Specific Gravity:	1.13 – 1.15
Appearance:	Dark Brown Liquid
Odor:	Slight Sulfite

- Meets FDA Regulation CFR Title 21 Part 173.310
- USDA Authorized – G 6

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Application

Oxytrol LD should be fed through a separate chemical feed system directly into the storage section of the deaerating heater, condensate receiver, or feedwater tank.

Oxytrol LD should not be mixed with alkaline boiler water treatment products.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.
GERMANTOWN, WI 53022

S
P
E
C
T
R
U
M®