

# OXYTROL®

## *Feedwater Oxygen Scavenger*

- Removes dissolved oxygen to prevent oxygen pitting
- Convenient, ready-to-use liquid

### General Description

**Oxytrol®** is a sodium sulfite based oxygen scavenger formulated to remove oxygen from steam boiler systems. **Oxytrol®** can be used in boilers with operating pressures up to 600 psi.

**Spectrum®** treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

### Specifications

|                   |                           |
|-------------------|---------------------------|
| Wt/Gallon:        | 9.59 lbs                  |
| pH:               | 9.5                       |
| Specific Gravity: | 1.150                     |
| Appearance:       | Water White, Clear Liquid |

- Meets FDA Regulation CFR Title 21 Part 173.310

### Handling

Recommended storage limit is 18 months.  
Keep container closed when not in use.

### Application

**Oxytrol®** can be added on a periodic basis through a bypass feeder on the feedwater line. Continuous feed with a chemical feed pump is recommended for optimum control.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022

S  
P  
E  
C  
T  
R  
U  
M®