

# OXYTROL™ DC-2

## *Catalyzed Feedwater Oxygen Scavenger*

- Removes dissolved oxygen to prevent oxygen pitting.
- Catalyzed; scavenges oxygen 20 - 500 times faster than commercial sulfites.
- Stabilized; catalyst activated only after product is dissolved in water.
- Powdered formulation for low use-cost protection.

### General Description

**Oxytrol DC-2** is a chemical oxygen scavenger formulated to remove oxygen from steam boiler systems. **Oxytrol DC-2** can be used in boilers with operating pressures up to 600 psi.

**Spectrum®** treatment products and programs are the key to long term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

### Specifications

Density:	90 lbs/ft <sup>3</sup>
pH (5% solution):	8.2
Appearance:	Light Tan/pink crystallized
Odor:	Slight sulfite

- Meets FDA Regulation CFR Title 21 Part 173.310.

### Handling

Recommended storage limit is 18 months.  
Keep container closed when not in use.

### Application

**Oxytrol DC-2** should be continuously fed to the storage section of the deaerating heater. Bypass feeding is acceptable providing the **Oxytrol DC-2** is fed separately and before the other chemicals are added.

Make solutions of 3 - 10% by weight using the lowest hardness water available or preferably condensate that has been cooled to 60-100°F. Mix only until dissolving is complete. Continuous agitation is not recommended. Polyethylene, stainless steel and fiberglass are preferred materials for solution tanks and pumps.

**Oxytrol DC-2** should be mixed separate from other boiler water chemicals.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022

S  
P  
E  
C  
T  
R  
U  
M®