

RUSTOSCALE[®]

14

Steam Boiler Treatment

- Prevents scale and corrosion to provide optimum boiler efficiency.
- Contains dispersants and conditioners to keep boiler sludge in a fluid, non-sticking form.
- Antifoams prevent carryover.
- Convenient, ready-to-use liquid.

General Description

Rustoscale 14 is specifically formulated to prevent scale and corrosion in steam boilers. It combines alkalinity adjustment, softening materials, antifoams and sludge conditioners to handle a variety of supply waters. The ingredients in **Rustoscale 14** meet FDA regulations for use in boilers producing steam that contacts food. It also meets USDA regulations for use in federally inspected meat and poultry plants.

Specifications

Wt/Gallon:	9.80 lbs
pH:	Greater than 12.5
Specific gravity:	1.175
Appearance:	Clear

- USDA Authorized - G 6
- Meets FDA Regulation CFR Title 21 Part 173.310

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Applications

The dosage of **Rustoscale 14** will depend on the make-up water analysis and the amount of makeup water added to the system. Dosage is controlled by periodic analysis of the boiler water. **Rustoscale 14** can be added on a periodic basis through a bypass feeder on the feedwater line. For high makeup boilers, an alkali resistant chemical feed pump is recommended.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.
GERMANTOWN, WI 53022