

# TOWERKLEEN 142

## *Cooling Tower Anti-Foulant*

- Highly effective proprietary product that breaks up biofilm
- Prevents deposits that can produce underdeposit corrosion problems and reduce heat transfer
- Add Towerkleen 142 three hours prior to any addition of an oxidizing biocide

### General Description

Effective biomass control coupled with superior organic suspension gives you the one-two punch needed for superior performance.

**Towerkleen 142** is one part of the **Spectrum®** water treatment system formulated to produce state-of-the-art results with state-of-the-art products.

**Spectrum®** treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

### Specifications

Wt/Gallon:	8.34 lbs
pH (conc):	6.0 – 7.0
Specific Gravity:	1.00
Appearance:	Clear Liquid, Slight Yellow

### Handling

Recommended storage limit is 18 months.  
Keep container closed when not in use.

### Applications

Prior to adding **Towerkleen 142** the system should have less than 0.1 ppm oxidizing biocide. **Towerkleen 142** should be used at 20 to 60 ounces per 1000 gallons of water capacity once or twice per week depending on the system.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022

S  
P  
E  
C  
T  
R  
U  
M®