

VOLTREET® PREFERRED

Condensate Line Treatment

- Blend of cyclohexylamine and morpholine
- Provides distribution throughout your boiler system
- Prevents carbonic acid corrosion of the condensate return system
- Convenient ready-to-use liquid formula
- Excellent choice for low pressure systems using steam for humidification

General Description

Voltreet Preferred is a blend of neutralizing amines formulated to prevent corrosion of condensate return lines.

Spectrum® treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

Specifications

Wt/Gallon:	8.325 lbs
pH:	> 11
Specific Gravity:	0.998
Appearance:	Clear, Slight Yellow Liquid
Odor:	Faint Amine

- Meets FDA Regulation CFR Title 21 Part 173.310

Handling

Recommended storage limit is 18 months.
Keep container closed when not in use.

Applications

The dosage of **Voltreet Preferred** will vary depending upon the formulation of the condensate system, the makeup water analysis and the amount of makeup water. **Voltreet Preferred** is controlled by maintaining the pH of the condensate in a slightly alkaline range.

Voltreet Preferred is added to the system continuously or on a periodic basis depending upon the system needs. It can be added to the boiler through a bypass feeder or a chemical feed pump.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.
GERMANTOWN, WI 53022