

# CST-10

## *Closed Recirculating System Treatment*

- Prevents oxygen pitting and corrosion in systems containing iron, steel, copper and their alloys
- Convenient, easy-to-use liquid
- Does not contain chromates
- Compatible with glycol based antifreeze products

### General Description

**CST-10** is a liquid chemical treatment formulated to prevent pitting and corrosion in closed recirculating water systems. **CST-10** is recommended for hot water boilers and most closed systems. When used as recommended, **CST-10** does not harm packing, valves, pumps, or mechanical seals.

**Spectrum®** treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum®** a part of your preventive maintenance program today.

### Specifications

Wt/Gallon:	9.68 lbs.
pH:	9.80
Specific Gravity:	1.155
Appearance:	Pale Yellow, Clear Liquid
Odor:	Organic

### Handling

Recommended storage limit is 18 months.  
Keep container closed when not in use.

### Application

#### Initial Dosage:

Add 1 gallon of **CST-10** to every 100 gallons of water in the system.

#### Maintenance:

After the initial dosage, occasional additions of **CST-10** may be required to maintain proper treatment levels. The additions will be determined by periodic water analysis and the amount of leakage from the system. **CST-10** may be added to the closed system through a bypass feeder on the recirculating line.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022