

# MP-283

## *Metal Passivator*

- Specially formulated to passivate steel and iron against oxygen attack
- Passivate new tubes after a partial or complete retubing
- Synergistic effect when used with sulfite oxygen scavenger

### General Description

**MP-283** when used in conjunction with sodium sulfite prevents new pitting and arrests corrosion at present pit sites.

Overall effectiveness of **MP-283** is directly dependent upon proper oxygen scavenger use and monitoring. **Spectrum**<sup>®</sup> treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum**<sup>®</sup> a part of your preventive maintenance program today.

### Specifications

Wt/Gallon:	8.42 lbs
pH (conc):	6.0 – 7.0
Specific Gravity:	1.02
Appearance:	Clear Liquid

- USDA Authorized - G 6
- Meets FDA Regulation: GRAS Status in CFR Title 21 Part 182.3041, Sub part D

### Handling

Recommended storage limit is 18 months.  
Keep container closed when not in use.

### Application

**MP-283** can be added on a periodic basis through a bypass feeder on the feedwater line. Continuous feed with a chemical feed pump is recommended for optimum control.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022