

# OXYTROL<sup>®</sup> LD

## *Feedwater Oxygen Scavenger*

- Removes dissolved oxygen to inhibit oxygen pitting
- Decharacterized for USDA inspected meat and poultry plants
- Convenient, ready-to-use catalyzed liquid

### General Description

**Oxytrol<sup>®</sup> LD** is a catalyzed oxygen scavenger formulated to remove oxygen from steam boiler systems with operating pressure up to 600 psi. **Oxytrol<sup>®</sup> LD** is decharacterized to meet USDA regulations for meat and poultry plants.

**Spectrum<sup>®</sup>** treatment products and programs are the key to long-term preventive maintenance. Make **Spectrum<sup>®</sup>** a part of your preventive maintenance program today.

### Specifications

Wt/Gallon:	9.5 lbs.
pH:	4.3 – 4.7
Specific gravity:	1.13 – 1.15
Appearance:	Dark Brown Liquid
Odor:	Slight Sulfite

- Meets FDA Regulation CFR Title 21 Part 173.310
- USDA Authorized – G6

### Handling

Recommended storage limit is 18 months.  
Keep container closed when not in use.

### Application

**Oxytrol LD** should be fed through a separate chemical feed system directly into the storage section of the deaerating heater, condensate receiver, or feedwater tank.

**Oxytrol LD** should not be mixed with alkaline boiler water treatment products.

Industrial Water Treatment By:



ALLIANCE GROUP, INC.  
GERMANTOWN, WI 53022

S  
P  
E  
C  
T  
R  
U  
M<sup>®</sup>